



Greenix™ PANEL COMPARISON WORKSHEET

| | Greenix™ Panel | Other Panel: |
|-----------------------------------|----------------|--------------|
| R-Values: | | |
| 4 ½" (wall) | R25 | _____ |
| 6 ½" (roof) | R40 | _____ |
| Polyurethane Core | Standard | _____ |
| HFC-245fa Polyurethane Foam | Standard | _____ |
| T&G Heavy Duty Connection | Standard | _____ |
| Cam-Lock Connection | Optional | _____ |
| Electrical Boxes Per Plan | Included | _____ |
| ¾" Conduit Per Plan | Included | _____ |
| MSR Rated Lumber | Standard | _____ |
| Framed & Foamed in Factory | Standard | _____ |
| Fabricated (Pre-cut) in Factory | Included | _____ |
| Wall Top Plates and Sill Flashing | Included | _____ |
| Wind Rating | 180 – 200+ MPH | _____ |
| Fire Rating | Class 1 | _____ |
| ICC Testing | Completed | _____ |
| Installation Manual | Included | _____ |
| Technical Support | Included | _____ |
| Panel Surface Options | | |
| Oriented Strand Board | Standard | _____ |
| Metal, Steel | Standard | _____ |
| Magnesium Board | Available | _____ |
| Fiber Reinforced Plastic (FRP) | Available | _____ |
| Fiberboard, Fiberrock | Available | _____ |